



Spec No. :DS23-2016-0103 Effective Date: 06/10/2017

Revision: A

LITE-ON DCC

RELEASE

BNS-OD-FC001/A4




1. Description

The LiteOn C03 LED is a revolutionary, energy efficient and ultra-compact new light source, combining the lifetime and reliability advantages of Light Emitting Diodes with the brightness of conventional lighting. It gives you total design freedom and unmatched brightness, creating a new opportunities for solid state lighting to displace conventional lighting technologies

Features

- I.C. compatible
- RoHS compliant and Pb free
- Lower operating costs
- Reduced maintenance costs

2. Outline Dimensions



Notes:

- All dimensions are in millimeters and dimension tolerances are ± 0.2mm except lens height and ceramic length / width dimension tolerance are ± 0.1mm
- Thermal pad of the device is electrically neutral from the anode and cathode pads

Part No.: LTPL-C035RH630 BNS-OD-FC002/A4



3. Absolute Maximum Ratings at Ta=25°C

Parameter	Symbol	Rating	Unit
DC Forward Current	If	700	mA
Power Consumption	Po	2.1	W
Operating Temp Range	Topr	-40 ~ +85	$\mathcal C$
Storage Temp Range	Tstg	-55 ~ +100	C
Junction Temperature	Tj	110	C

Notes:

Operating the LED under reverse bias condition long time might result in damage or failure of the component.



4. Electro-Optical Characteristics at Ta=25℃

Parameter	Symbol	Values		Test Condition	Unit
		Min.	1.6		
Forward Voltage	Vf	Тур.	2.3	If = 350mA	V
		Max.	2.6		
Radiant Flux		Min.	250	If = 350mA	
	Фе	Тур.	325		mW
		Max	400		
Dominant Wavelength	14/-/	Min.	620	16 250mA	
	Wd N	Max	640	If = 350mA	nm
Viewing Angle	2θ1/2	Тур.	130	If = 350mA	o

Notes:

Radiant flux (mW) is the total Radiant flux output as measured with an integrating sphere.



5. Bin Code List

Specific Lighting LTPL-C035RH630

Vf : Forward Voltage Spec. Table			
Vf Bin	Vf (V) @ If = 350mA		
	Min.	Max.	
V0	1.6	1.8	
V1	1.8	2.0	
V2	2.0	2.2	
V3	2.2	2.4	
V4	2.4	2.6	

Forward Voltage Tolerance: +/- 0.1 V

Г			
arPhi e : Radiant Flux Spec. Table			
Φe Bin	Φe (mW) @ $If = 350$ mA		
	Min.	Max.	
L1	250	280	
L2	280	310	
L3	310	340	
L4	340	370	
L5	370	400	

Radiant Flux Tolerance: +/- 10%

Wd: Dominant Wavelength Spec table			
M/d Dia	Wd (nm) @ If = 350mA		
<i>Wd</i> Bin	Min.	Max.	
D6E	620	625	
D6F	625	630	
D6G	630	635	
D6H	635	640	

Dominant Wavelength Tolerance: +/- 3nm

Notes:

Bin classification code is marked on each packing bag.



6. Typical Electrical / Optical Characteristics Curves

(25°C Ambient Temperature Unless Otherwise Noted)




Fig 1. Relative Flux vs. Forward Current




Fig 2. Relative Spectral Distribution






Fig 3. Radiation Characteristics




Fig 4. Forward Current vs. Forward Voltage






Fig.5 Relative Radiant Flux vs Junction Temperature




Fig.6 Dominant Wavelength vs Forward Current






Fig.7 Delta Voltage vs Junction Temperature





Fig.8 Dominant wavelength vs Junction Temperature



7. User Guide

Suggested Reflow Soldering Characteristics



Notes:

- 1. All temperatures refer to topside of the package, measured on the package body surface.
- 2. The soldering profile could be further referred to different soldering grease material characteristic. The grease vendor will provide this information.
- 3. A rapid-rate process is not recommended for the LEDs cooling down from the peak temperature.
- 4. Although the recommended reflow conditions are specified above, the reflow or hand soldering condition at the lowest possible temperature is desirable for the LEDs.
- 5. LiteOn cannot make a guarantee on the LEDs which have been already assembled using the dip soldering method.



7. Reliability Test Plan

No	Test item	Condition	Duration	Number of Failed
1	Low Temperature Operating Life (LTOL)	$Tc = -10^{\circ}C$, $If = 350$ mA	1000 hrs	0/10
2	Room Temperature Operating Life (RTOL)	25℃, <i>If</i> = 350mA	1000 hrs	0/10
3	High Temperature Operating Life (HTOL)	Tc=85°C, $If=60$ mA	1000 hrs	0/10
4	Wet High Temperature Operating Life (WHTOL)	60℃/90%RH, <i>If</i> = 350mA	500 hrs	0/10
5	Non-Operating Thermal Shock (TMSK)	-40℃ to 125℃ 30 minutes dwell, <10 seconds transfer	100 cycles	0/10
6	High temperature storage	<i>T</i> _A =100℃	1000 hrs	0/10
7	Resistance to Soldering Heat (Reflow Soldering)	(Pre-store @ 25℃, 60 ±5% RH for 168hrs) TSId = 260℃, 10 sec	2 times	0/10
8	Solderability Test	245'C, 5sec Pb free solder, wetting >95%	1 time	0/10

Notes:

- 1. Operating life test are mounted on thermal heat sink
- 2. Storage item are only component, not put on heat sink.


Criteria for Judging the Damage

Item	Symbol	Test Condition	Criteria for Judgment			
	Symbol	rest Condition	Min.	Max.		
Forward Voltage	Vf	If = Typical Current	-10%	+10%		
Radiant Flux	Фе	If = Typical Current	-15%	+15%		

Part No. : LTPL-C035RH630 BNS-OD-FC002/A4



Recommend Printed Circuit Board Attachment Pad




Notes:


- The LEDs can be soldered using the reflow soldering or hand soldering method. The recommended hand soldering condition is 300℃ max. and 2secs max. on ly once, and the operation of reflow soldering is only up to three times at maximum.
- 2. All temperatures refer to topside of the package, measured on the package body surface.
- 3. The soldering profile could be further referred to different soldering grease material characteristic. The grease vendor will provide this information.
- 4. A rapid-rate process is not recommended for the LEDs cooling down from the peak temperature.
- 5. Although the recommended reflow conditions are specified above, the reflow or hand soldering condition at the lowest possible temperature is desirable for the LEDs.
- LiteOn cannot make a guarantee on the LEDs which have been already assembled using the dip soldering method.



Package Dimensions of Tape



Package Dimensions of Reel



Notes:

- 1. Empty component pockets sealed with top cover tape.
- 2. 7 inch reel-maximum 500 pieces per reel.
- 3. The maximum number of consecutive missing lamps is two.
- 4. In accordance with EIA-481-1-B specifications.

Part No. : LTPL-C035RH630 BNS-OD-FC002/A4



8. Cautions

Cleaning

Use alcohol-based cleaning solvents such as isopropyl alcohol to clean the LED if necessary.

Do not use unspecified chemical liquid to clean LED, it could harm the package.

Drive Method

An LED is a current-operated device. In order to ensure intensity uniformity on multiple LEDs connected in parallel in an application, it is recommended that a current limiting resistor be incorporated in the drive circuit, in series with each LED as shown in Circuit below.



Circuit model A

Circuit model B

- (A) Recommended circuit.
- (B) The brightness of each LED might appear different due to the differences in the I-V characteristics of those LEDs.
- © This LED should be used under forward current, particularly not used under continuous reverse current to avoid the damage to LED.

The electrode pads are plated with gold, but it is still not recommended to the use under any of the following conditions, please confirm the performance and reliability are well enough if you use it under any of the following conditions

- Do not use sulfur-containing materials in commercial products including the materials such as seals and adhesives that may contain sulfur.
- Do not put this product in a place with a lot of moisture (over 85% relative humidity), dew condensation, briny air, and corrosive gas (CI, H2S, NH3, SO2, NOX, etc.).

Manual Handling Remark

The LED should only be picked up by making contact with the sides of the LED body. It should not put any pressure on the lens either by finger or any hand tool. Do not puncture or push the lens.



ESD (Electrostatic Discharge)

Static Electricity or power surge will damage the LED. Suggestions to prevent ESD damage:

- Use a conductive wrist band or anti-electrostatic glove when handling these LEDs.
- · All devices, equipment, and machinery must be properly grounded.
- · Work tables, storage racks, etc. should be properly grounded.
- · Use ion blower to neutralize the static charge which might have built up on surface of the LED's plastic lens as a result of friction between LEDs during storage and handling.

ESD-damaged LEDs will exhibit abnormal characteristics such as high reverse leakage current, low forward voltage, or "no light up" at low currents. To verify for ESD damage, check for "light up" and V_F of the suspect LEDs at low currents. The V_F of "good" LEDs should be >1.0V@0.5mA.

Training and Certification

- 1. Working area is ESD-certified.
- Training records and re-certification dates monitored.

Static-Safe Workstation & Work Areas

- 1. Static-safe working stations or work-areas have ESD signs.
- 2. All surfaces and objects at all static-safe workstation and within 1 ft measure less than 100V.
- 3. All ionizer activated, positioned towards the units.
- Each work surface mats grounding is good.

Personnel Grounding

- Every person (including visitors) handling ESD sensitive (ESDS) items wear wrist strap, heel strap or conductive shoes with conductive flooring.
- 2. If conductive footwear used, conductive flooring also present.
- Garments, hairs or anything closer than 1 ft to ESD items measure less than 100V. 3.
- The wrist strap or heel strap/conductive shoes are checked daily and result recorded. 4.
- All wrist strap or heel strap checkers calibration up to date.

Device Handling

- Each ESDS items identified by EIA-471 labels on item or packaging.. 1.
- No static charge generators (e.g. plastics) inside shielding containers with ESDS items. 2.
- 3. All flexible conductive and dissipative package materials are inspected before reuse or recycles

Part No.: LTPL-C035RH630 BNS-OD-FC002/A4





Storage

This product is qualified as Moisture sensitive Level 3 per JEDEC J-STD-020 Precaution when handling this moisture sensitive product is important to ensure the reliability of the product.

The package is sealed:

The LEDs should be stored at 30℃ or less and 85%RH or less. And the LEDs are limited to use within one year, while the LEDs is packed in moisture-proof package with the desiccants inside.

The package is opened:

The LEDs should be stored at 30°C or less and 60%RH or less. The LEDs are limited to solder process within 168hrs. If the Humidity Indicator shows the pink color in 10% even higher or exceed the storage limiting time since opened, we recommended to baking LEDs at 60°C at least 24hours before solder. To seal the remainder LEDs return to package, it's recommended to be with workable desiccants in original package.

Part No. : LTPL-C035RH630 BNS-OD-FC002/A4





9. Datasheet Version:

Version	Date	Owner	Change Item	
1	2016/09/03	ChunChieh	Initial specification	
1.1	2016/10/21	ChunChieh	Update Bin table	P.4
1.2	2016/11/28	ChunChieh	Add Electrical / Optical Characteristics Curves Fig. 6,7,8	P. 7,8
1.3	2017/03/09	ChunChieh	Add polarity mark in PKG and Carrier page	P.1,12
2	2017/03/22	ChunChieh	Change Flux spec from "lm" to "mW"	P.4